

SAFETY DATA SHEET

In according 3rd revision GHS

Revision Date: 26 April 2018

Section 1 - Identification

Product Name : BC05B

Product Type : Block-co polypropylene

Product Use : Injection Molding Application

Manufacturer : IRPC Public Company Limited

299 Moo. 5 Sukhumvit Road, Amphur Muang, Rayong THAILAND

Emergency Call : +66(0) 38802560

Website : www.irpc.co.th, www.irpcmarket.com

Section 2 - Hazards Identification

Classification according to Regulation (EC) No. 1272/2008 (CLP) and GHS Classification:

This product is not classified as dangerous according to Regulation (EC) No 1272/2008 and GHS

Pictogram: Not Applicable

Signal Word: Not applicable

Hazard Statement:

_

Precautionary Statement:

Section 3 - Composition / Information on Ingredients

Chemical Name		CAS Number	EC Number	Percent weight
Polypropylene		9003-07-0	Polymer	>= 80
Propylene Ethylene Copolyme	er	9010-79-1	Polymer	<= 20

Section 4 - First-aid Measures

Skin Exposure If molten material comes in contact with the skin, cool under ice water or a

running stream of water.DO NOT attempt to remove the material from the skin.Remove could result in serve tissue damage.Get medical attention.

Eyes Exposure If molten material should splash into eyes, flush eyes immediately with

fresh water for 15 minutes while holding the eyelid open. Remove contact

lenses, if worn.Get immediate medical attention.





Inhalation : Move the exposed person to fresh air.If breathing is difficult, give

oxygen.Get medical attention if breathing difficulties continue.

Ingestion : Not a probable route of exposure. If person is conscious, rinse mouth with

water.Do not induce vomiting unless directed to do so by a physician.

Section 5 - Fire-fighting Measures

Suitable extinguishing agents : Dry chemical, foam, water fog or carbon dioxide. Avoid using direct

streams of water on molten burning material.

Hazards during fire-fighting : Carbon monoxide, carbon dioxide, hydrogen cyanide.Carbon

monoxide, carbon dioxide, hydrogen cyanide.

Protective equipment: Use a mask with universal filler. Use self-contained breathing

apparatus and full protective clothing.

Section 6 - Accidental Release Measures

Personal precautions : Avoid inhalation and direct contact.

Environmental precautions: Discharge into the environment must be avoided.

Cleanup:

Collect spilled material using a method that minimizes dust generation (e.g., wet methods, HEPA vacuum). Place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

Section 7 - Handling and Storage

Handling : with adequate ventilation. Avoid dust generation. Accumulations of

: should be removed from settling areas.

Storage conditions : Store in a cool, dry, well-ventilated area or silo away from sources

of heat, flame and sparks. Ventilate enclosed storage areas, such

as trailers and railcars, before entering.

Section 8 - Exposure Controls / Personal Protection

Exposure limits

Component Name	Reference	TWA		STEL	
component Name	Reference	ppm	mg/m3	ppm	mg/m3
Polypropylene	Canada-OEL	-	10	-	-
	Italy-OEL	-	10	-	-
Propylene Ethylene copolymer	Canada-OEL	-	10	-	-
	Italy-0EL	-	10	-	-

Personal protective equipment

Respiratory protection : No special respiration protection is normally required.

Eye protection Wear safety glasses with side shields, goggles or face shield.





Protective clothing : Gloves required when handling hot material. In case of fire, wear

MSHA/NIOSH approved self-contained breathing apparatus or

equivalent and full protective gear.

Ventilation Provide adequate ventilation when processing material at elevated

temperatures.

Other protective equipment : Ensure that eyewash stations and safety showers are proximal to the

work-station location.

Engineering Controls : For molten materials: Provide mechanical ventilation; in general such

ventilation should be provided at compounding/converting areas and at fabricating/filling work stations where the material is heated.Local

exhaust ventilation should be used over and in the vicinity of machinery involved in handling the molten material.

Section 9 - Physical and Chemical Properties

Appearance : Colorless and opaque pellets

Odour : None

Boiling Point : Not Applicable

Flash Point : Not Applicable

Melting Point : 130-170°C

Vapour Pressure : Not Applicable

Auto ignition temperature : Not Applicable

Solubility : Insoluble in water

Viscosity : Not Applicable

Upper/Lower flammability or explosive

limit

Not Applicable

pH : Not Applicable

Relative density : Not Applicable

Specific Gravity : Not Applicable

Partition coefficient: **n-octanol**/**water** : Not Applicable

Decomposition temperature : Not Applicable

Explosive properties : Not Applicable

Section 10 - Stability and Reactivity

Stability : No chemical reactivity under normal ambient and anticipated handling

conditions of temperature and pressure.

Condition to Avoid : Avoid heating above the recommended processing temperature.

Material to Avoid : May react with strong oxidizing agents, such as chlorates, nitrates,

peroxides, etc.May react with free halogens.

Dangerous decomposition: Small quantities of low molecular weight hydrocarbons, carboxylic acids,

carbon oxides can be formed during thermal processing.





Section 11 - Toxicological Information

Acute Toxicity

Chemical name	Route	Species	Acute Toxic Value	
Polypropylene	Oral	Rat	LD50 > 8,000 mg/kg	

Irritating/corrosive effects

Eye Irritation Solid particles may cause transient irritation from mechanical abrasion.

Skin Irritation : Molten material may cause thermal burns.

Inhalation : Process fumes may cause irritation.

Ingestion May cause a choking hazard if swallowed.

Section 12 - Ecological Information

Eco-toxicity : No relevant studies found.

Persistence and degradability: This material is not expected to be readily biodegradable.

Bio-accumulative potential Product is not likely to accumulate in biological organisms.

Mobility in soil . No relevant studies identified.

Other adverse effects This substance is not in Annex I of Regulation (EC) 2037/2000 on

substances that deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal methods:

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. Dispose of by: burial in a land-fill specifically licensed to accept chemical and/or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material) Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.





Section 14 - Transport Information

Regulatory information	UN number	Classes	Packing group	Label	Additional information
DOT	-	-	-	-	-
ADR/RID	-	-	-	-	-
IMDG CODE	-	-		-	-
ICAO/IATA	-	-	-	-	-

Section 15 - Regulatory Information

US Toxic Substances Control Act

All components of this product are on the TSCA Inventory.

European Inventory of Existing Commercial Chemical Substances (EINECS)

The components of this product are on the EINECS inventory or are exempt from inventory requirements.

Canada - WHMIS

This product does not meet WHMIS classification criteria.

NFPA – USA

Health: 0 Flammability: 1 Reactivity: 0

HMIS

Health: 0 Flammability: 1 Reactivity: 0

Section 16 - Other Information

DOT : Department of Transportation

ADR : European agreement concerning the international carriage of dangerous

goods by road.

RID : Regulations concerning the international carriage of dangerous goods by

rail

IMDG-CODE : International maritime dangerous goods code

ICAO : International Civil Aviation Organization
IATA : International air transport association

GHS : Globally Harmonized System of Classification and Labeling of Chemicals

NFPA : National Fire Protection Association

HMIS : Hazardous Materials Identification System

WHMIS : Workplace Hazardous Materials Information System





TWA : Time Weighted Average

LD50 : Lethal Dose, 50%

The information above is believed to be accurate and represents the best of our knowledge, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.

